GREENWAY



Presents:





Industrial & Maritime Coatings

Anti-Corrosion · Impermeable · Mold & Mildew Resistant

MAD PRODUCTS LEAD THE WAY IN:

- LONG-TERM ASSET LIFE PROTECTION AND EXTENSION
- LOWERING MAINTENANCE AND FACILITIES COSTS
- REDUCING ENERGY COSTS
- APPLICATION ON 99% OF ALL SUBSTRATES





The Discovery Channel selected MAD Products out of 900 exhibitors at the 2015 GREENBUILD INTERNATIONAL EXPO in Washington, D.C. as the breakout product of the show



Marine Grade PRODUCT LINE

- MAD ARMOR Substrate Protection, Waterproofing, Roofing
- MAD SHARK Non-Skid Flooring
- MAD GRIP Non-Skid Handrail Protection
- MAD DEFENSE Rust Converter and Primer
- MAD BOND Bonding Agent and Primer for Porous Surfaces
- MAD FIBER Fibrous Filler for Filling & Repairing Surfaces



General Characteristics of MAD COATINGS

MAD ARMOR

MAD SHARK

MAD GRIP

- All green water based products
- Low VOC and Odorless Application
- UV Stable
- Water, Snow and Ice Repellent
- Flame Resistant

- Rust preventative
- Water Repellant
- Outlasts other products up to 2x
- 5 Year Shelf Life





Advanced marine-grade coating for superior substrate protection

USES:

- Equipment & Fixtures
 - HVAC units, cooling towers, fan rooms, plenums & ducts
 - Hot/cold piping and drains
 - Expansion Joints
- Interior & Exterior
 - Walls, Floors & Ceilings
 - Flexible insulation (e.g., Armor Flex)
- Roofs (cooling, waterproofing, ponding water)
- 99% of all substrates (rust/corrosion prevention, waterproofing, energy conservation)

- Rust, Mold & Mildew Preventative
 - Maintains Surface Temp below 105F / 400
 - Full Spectrum Freeze & Thaw Cycle
 - High Reflectivity (97.3%)
 - Acid Resistant
 - 700% Elongation









Advanced water-proof non-skid marine-grade flooring

- Rust, Mold & Mildew Preventative
 - Full Spectrum Freeze & Thaw Cycle
 - · Available in 18 to 220 grit
 - 15,000 PSI tensile strength
 - #9 on hardness scale
 - Acid Resistant

USES:

MAD Shark coats, insulates and protects:

- Floors
 - Kitchen, Service area, Fan rooms, Generator rooms, Walkways)
 - Pretty much any floor you need to have a non-skid coating!

APPLICATION:

- MAD Shark is used in conjunction with MAD Armor
- Coverage (used in conjunction with MAD Armor)
 - Limited Traffic Area 1 Gallon = 100 Sq. Ft. (with 1 gallon of MAD Armor)
 - Heavy Traffic Area 1 Gallon = 50 Sq. Ft. (with 1 gallon of MAD Armor per 50 sq. ft.)





Superior non-slip hand rail protection

- No Need for Surface Preparation
 - Available in various grits

USES:

MAD Grip can be used to coat, insulate and protect:

- Hand rails (stairs, balconies, marinas, ramps, walkways)
- Pretty much anything you need to have a non-slip coating!

APPLICATION:

- MAD Grip is used in conjunction with MAD Armor
- Coverage 1 Gallon = 100 Sq. Ft. / 9M²





General Characteristics of MAD PRIMERS

MAD DEFENSE

MAD BOND

- All green water based products
- Low VOC
- Odorless Application
- No need for extensive surface prep. (reduced labor costs)

- Flame Resistant
- Rust preventative
- Single Component



Both products can be used in conjunction with Mad Armor



Specialty rust converter and primer

USES:

- MAD Defense can be used to treat, coat and protect existing rust problems:
 - Applies directly over the rust area
 - Converts rust to non-corrosive substrate
 - Pretty much anywhere you have rust!

APPLICATION:

- Coverage 1 Gallon = 300 Sq. Ft. / 28M²
- 2 Year Shelf Life

- UV stable
 - Flame Resistant
 - Acid Resistant





Specialty bonding agent and primer

USES:

MAD Bond can be used to coat porous substrates for priming of topcoat:

- Applies directly over porous substrates to enhance adhesion of Mad Armor or Shark
- **APPLICATION:**
- Coverage 1 Gallon = 300 Sq. Ft. / 28M²
- 1 year shelf life

- Mold & Mildew Preventative
 - Flame Resistant
 - Acid Resistant
 - Gas Barrier





Specialty fiber filler for filling & repairing surfaces

USES:

MAD Fiber can be used to repair and build up HVAC insulation blankets and to repair small pin hole corrosion points in ducting:

- Hydrophobic surface
 - UV Stable
 - Flame Resistant
 - Acid Resistant
 - Gas Barrier

APPLICATION:

- Coverage 1 Gallon = 100 Sq. Ft. / 9.3M²
- 5 year shelf life



Who's Using MAD Products Today?























Global Third-Party Independent Endorsements













Images of MAD Products





Pliability of MAD Armor coated flexible insulation – After treatment insulation is FULLY ENCAPSULATED, Flexible and PROTECTED from further degrading or dry rot from element exposure.





Insulated HVAC air conditioning plenum coming off air handling unit.





MAD Armor protecting Armor-Flex Insulation

AC Ducts







Air intake rust and corrosion due to weather elements.



Air ducts (inside) rust and corrosion due to salt air and moisture.





Fully protected and converted rusted pipe.

Ash Collection Room – Incinerator Facility

• Muriatic acid is sprayed throughout the room on a daily basis







MAD Shark ensures safe environment that protects floor surfaces.



Before



After

MAD Shark ensures safe environment that protects floor surfaces.



Before



After

Protects and seals roofs to withstand ponding water




Before



After

Protects and seals roofs to withstand ponding water





Thermal image of RV roof showing MAD Armor keeping it cool.

For more information about MAD Products and to set up a demonstration please contact:





brucev@greenwaytechnologies.com